

NOTE: June 2002: The specifications listed below are shown for reference only. Honda camshafts are no longer manufactured by Andrews Products and we have no existing inventory.

**ANDREWS PRODUCTS, INC.
431 Kingston Ct.
Mt. Prospect IL 60056
847-759-0190**

TIMING SPECIFICATIONS (CB500 / 550 / 650)

GRIND	TIMING	DURATION(1)	LIFT(2)	LASH
Stock int.	2/32	214 deg.	.292	(timing listed for comparison)
Stock exh.	37/3	220 deg.	.278	
#11	8/40	228 deg.	.315	.004
	40/8	228 deg.	.315	.004
#16	18/46	244 deg.	.350	.004
	46/18	244 deg.	.350	.004

TIMING SPECIFICATIONS (CB500 / 550 / 650)

GRIND	TIMING	DURATION(1)	LIFT(2)	LASH
A	20/40	240 deg.	.345	.004
	40/20	240 deg.	.345	.004
D	19/45	244 deg.	.385	.004
	45/19	244 deg.	.360	.004
K	35/63	278 deg.	.370	.004
	63/35	278 deg.	.370	.004
4	32/68	280 deg.	.400	.004
	68/32	280 deg.	.400	.004

(1) Measured at .050 valve lift.

(2) Max. valve lift at 0 lash.

DEC/82